

CONTENTS

Acknowledgements	vi
1. Introduction	1
2. Fundamentals of porous silicon and applications	5
2.1. History of porous silicon	6
2.2. Basics of the porous silicon formation process	7
2.2.1. Electrochemical etching of silicon	7
2.2.2. Porous silicon formation chemistry	10
2.2.3. Pore size and morphology	13
2.2.4. Anodization parameters	16
2.2.5. Photoluminescence of porous silicon	18
2.3. Applications of porous silicon	19
2.3.1. Distributed Bragg Reflectors	20
2.3.2. Microcavities	23
2.3.3. Rugate filters	24
2.3.4. Omnidirectional mirrors	24
2.3.5. Waveguides	25
2.3.6. Sensors	25
2.3.7. Other applications	26
3. Simulation programs for the analysis of multilayer media	27
3.1. Mathematical methods for the analysis and simulation of multilayers	28
3.1.1. Transfer matrix method (TMM)	28
3.1.1.1. Reflectance and transmittance	31
3.1.1.2. Bloch waves and band structures	32
3.1.1.3. Advantages and drawbacks of the TMM	34
3.1.2. Plane wave method	35
3.1.3. Finite Difference Time Domain	36

3.2. Development of the simulation programs	37
3.2.1. Program for the calculation of reflectivity, transmission and absorption spectra.	37
3.2.2. Program for the calculation of photonic band diagrams	41
3.3. Performance of the developed programs for the study of optical devices	45
3.3.1. Distributed Bragg Reflectors	45
3.3.1.1. Performance of the developed programs for the simulation of DBRs	45
3.3.1.2. Study of the DBR parameters	47
3.3.1.3. Design of a porous silicon DBR for 1.55 μ m applications	50
3.3.1.4. Reflectivity spectrum of stacked filters	51
3.3.2. Microcavities	52
3.3.2.1. Performance of the developed programs for the simulation of microcavities	52
3.3.2.2. Study of the microcavities parameters	53
3.4. Summary and conclusions	56
4. Analysis and design of optical devices based on porous silicon multilayers	59
4.1. Omnidirectional mirrors (OM)	60
4.1.1. Periodic OM	60
4.1.1.1. Refractive indices n_H and n_L	60
4.1.1.2. Thickness of one layer (h_H) and period thickness (Λ) ratio: (h_H/Λ)	64
4.1.1.3. Number of periods	67
4.1.1.4. Omnidirectional mirror with a periodic structure for 1.55 μ m applications	68
4.1.2. Chirped OM	70
4.1.2.1. Omnidirectional mirror with chirped structure for 1.55 μ m applications	71

4.1.3. Random OM	72
4.1.3.1. Random omnidirectional mirror for 1.55 µm applications	77
4.1.4. New enlarged omnidirectional bandgap mirrors	78
4.1.4.1. Porous silicon balanced and unbalanced mirrors ...	80
4.1.4.2. Porous silicon balanced mirror for 1.55 µm applications	82
4.1.4.3. Porous silicon unbalanced mirror for 1.55 µm applications	82
4.1.5. Comparison of the studied mirror structures	84
4.2. Waveguides	86
4.2.1. Total internal reflection waveguides	86
4.2.1.1. Total internal reflection principles	87
4.2.1.2. Porous silicon slab waveguides for 1.55 µm applications	90
4.2.2. Photonic crystal waveguides	94
4.2.2.1. Structure	94
4.2.2.2. Determination of the parameters n_0 , d_H and N	95
4.2.2.3. Omnidirectional mirrors and DBR as cladding for porous silicon planar waveguides	99
4.2.2.4. Modes of the multilayer waveguide	104
4.3. Conclusions	107
5. Fabrication and characterization of porous silicon layers	111
5.1. Fabrication System	112
5.1.1. Electrochemical cell	113
5.1.1.1. Lateral-wafer electrochemical cell	113
5.1.1.2. Bottom-wafer electrochemical cell	116
5.1.2. Source for growth control	119
5.1.2.1. Voltage source	120
5.1.2.2. Current source	121
5.1.3. Control Program	122

5.1.4. Electrolyte	124
5.1.5. Silicon wafers and sample preparation	124
5.1.6. Fabrication of porous silicon monolayers and multilayers ...	127
5.2. Characterization of the fabricated porous silicon layers.....	129
5.2.1. Measurement techniques	130
5.2.1.1. Scanning Electron Microscopy	130
5.2.1.2. Fourier Transform Infrared Spectroscopy	131
5.2.1.3. Spectroscopic Ellipsometry	132
5.2.1.4. Atomic Force Microscopy	133
5.2.2. Mathematical methods for the determination of the refractive index and thickness	134
5.2.2.1. Measurement of interference fringes	134
5.2.2.2. Spectrum analysis fitting	138
5.3. Calibration of the fabrication system (Anodization parameters)	141
5.3.1. Current density-refractive index relation	141
5.3.2. Current density-porosity relation	144
5.3.3. Etching time-thickness relation	145
5.4. Conclusions	147
 6. Ellipsometric study of porous silicon layers	151
6.1. Introduction to spectroscopic ellipsometry	152
6.1.1. Fundamentals of ellipsometry.....	153
6.1.2. Equipments for ellipsometric measurements. Ellipsometers	156
6.2. Ellipsometric characterization process	157
6.2.1. UVISEL Ellipsometer	157
6.2.2. Influence of the spot size on the ellipsometric measurements	158
6.2.3. Process for the determination of porous silicon characteristics using ellipsometric data	161
6.3. Measurement and characterization of porous silicon monolayers ...	163
6.3.1. Isotropic optical model	163
6.3.2. Anisotropic optical model	169

6.3.3. Depolarization of the porous silicon monolayers	176
6.3.4. Summary	177
6.4. Characterization of porous silicon multilayers	179
6.4.1. One period multilayer.....	180
6.4.2. Two period multilayer	182
6.4.3. Three period multilayer	184
6.5. Conclusions	186
7. Optical devices based on porous silicon multilayers	189
7.1. Distributed Bragg Reflector	190
7.1.1. Fabrication and characterization	190
7.1.2. Simulation	192
7.2. Microcavity	195
7.2.1. Fabrication, characterization and simulation	195
7.2.2. Influence of the relative humidity on the reflectivity spectrum	197
7.2.3. Water condensation on the surface of the microcavity	199
7.3. Omnidirectional mirrors	201
7.3.1. Design, fabrication and characterization of periodic structures	201
7.3.2. Design of a new omnidirectional mirror structure	204
7.3.3. Fabrication and characterization of the new omnidirectional mirror structure	207
7.3.4. Enlargement of the omnidirectional bandgap	211
7.4. Conclusions	216
8. Summary and Conclusions	219
References	225
Publications related to this thesis	241

UNIVERSITAT ROVIRA I VIRGILI
DESIGN, FABRICATION AND CHARACTERIZATION OF POROUS SILICON MULTILAYER OPTICAL DEVICES
Elisabet Xifré Pérez
ISBN: 978-84-691-0362-3 /DL: T.2181-2007

Acknowledgments

I would like to express my deepest gratitude to my directors Dr. Josep Pallarès and Dr. Lluís Marsal for their guidance, support, encouragement and invaluable advices throughout these years in all aspects of the work. Without them this work was not possible. My more sincere thanks for both.

My special gratitude also to Dr. Josep Ferré for his suggestions, discussions, simulations and help with the FTIR measurements. And also for his very valuable hints and his guidance in mathematical and physics aspects that were essential for the development of all this work.

I am grateful to Dr. Enric Garcia-Caurel for his kindness that made possible my stage at the Ecole Polytechnique and all his help during the three months that I was there and until the defense of this thesis. His experience and knowledge of the ellipsometric techniques have permitted to realize a really interesting work.

I would also like to thank all the people of the Departament d'Enginyeria Electrònica, Elèctrica i Automàtica of the Universitat Rovira i Virgili, especially to Dr. Alfonso Romero for his guidance and his help with LabView control and also for his support, together with Dr. Xavier Correig at the beginning of my work at the University.

Many thanks are also given to the colleagues in the NePhoS group for their friendship and support, especially to Lukas for all his help with the samples and to Ivan and Mikhail. I wish to specially thank to Dr. Trifon Trifonov for teaching me how to make porous silicon layers and for all his help during the beginning of this work.

I would like to thank to all my doctoral companions for being such excellent colleagues. Especially to Raul for all his help and support, and to Edwin, Alexander, Mariona, Stella and Radu.

Many thanks to Mercè and Mariana for their help and guidance with the SEM equipment.

My deepest love to my parents for all their support, help and great patience.

I would like to acknowledge the Universitat Rovira i Virgili for the doctoral fellowship that made it possible to conduct the doctoral work.

This work has been supported by the Ministerio de Educación y Ciencia under grant numbers TIC2002-04184-C05, TEC2005-02038 and TEC2006-06531.